

PN 2,5

Jmenovitá světlost Nominal diameter	Jmenovitá světlost Nominal diameter	Úhlový posuv Angular movement	Ohybová tuhost Angular spring rate	Třecí moment Frictional moments
DN	DN	± deg (°)	N.m/°	N.m/bar
mm	inch			
50	2"	6,0	0,8	0,3
50	2"	12,0	0,4	0,3
65	2 ½"	6,0	0,8	0,5
65	2 ½"	12,0	0,4	0,5
80	3"	3,0	1,0	0,7
80	3"	6,0	0,6	0,7
80	3"	12,0	0,4	0,7
100	4"	3,0	4,9	1,1
100	4"	6,0	2,7	1,1
100	4"	12,0	1,9	1,1
125	5"	3,0	17,0	2,0
125	5"	6,0	9,6	2,0
125	5"	2,0	6,7	2,0
150	6"	3,0	33,0	2,8
150	6"	6,0	18,0	2,8
150	6"	12,0	13,0	2,8
200	8"	3,0	41,0	4,7
200	8"	6,0	23,0	4,7
200	8"	12,0	16,0	4,7
250	10"	3,0	66,0	7,2
250	10"	6,0	36,0	7,2
250	10"	12,0	25,0	7,2
300	12"	2,0	92,0	13,0
300	12"	4,0	51,0	13,0
300	12"	6,0	36,0	13,0
350	14"	2,0	92,0	16,0
350	14"	4,0	51,0	16,0
350	14"	6,0	35,0	16,0
400	16"	2,0	223,0	21,0
400	16"	4,0	160,0	21,0
400	16"	6,0	102,0	21,0
500	20"	2,0	540,0	33,0
500	20"	4,0	386,0	33,0
500	20"	6,0	246,0	33,0
600	24"	2,0	820,0	69,0
600	24"	4,0	585,0	69,0
600	24"	6,0	373,0	69,0
700	28"	1,5	1 440,0	94,0
700	28"	2,0	960,0	94,0
700	28"	4,0	640,0	94,0
800	32"	1,5	1 918,0	162,0
800	32"	2,0	1 278,0	162,0
800	32"	4,0	852,0	162,0
900	36"	1,5	2 449,0	255,0
900	36"	2,0	1 633,0	255,0
900	36"	4,0	1 088,0	255,0



MWP

Stavební délka Overall length	Šířka Width	Přibližná hmotnost App. weight
mm	mm	kg
260	220	8,0
310	220	8,0
310	230	10,0
360	230	10,0
310	250	12,0
350	250	13,0
390	250	13,0
310	310	17,0
360	310	18,0
410	310	19,0
310	340	20,0
360	340	21,0
410	340	23,0
320	380	27,0
370	380	29,0
420	380	31,0
340	450	40,0
400	450	43,0
460	450	45,0
350	520	51,0
410	520	55,0
470	520	58,0
370	570	75,0
440	570	80,0
500	570	85,0
380	630	85,0
450	630	90,0
520	630	95,0
450	730	125,0
500	730	130,0
590	730	135,0
480	830	165,0
530	830	175,0
620	830	185,0
480	950	210,0
530	950	220,0
620	950	235,0
460	1 100	260,0
500	1 100	270,0
570	1 100	285,0
460	1 260	310,0
500	1 260	320,0
570	1 260	335,0
480	1 370	415,0
520	1 370	425,0
590	1 370	440,0



MFP

Stavební délka Overall length	Šířka Width	Přibližná hmotnost App. weight
mm	mm	kg
90	210	6,0
140	210	6,0
100	230	7,0
150	230	8,0
100	260	10,0
140	260	10,0
180	260	11,0
110	320	13,0
150	320	14,0
200	320	15,0
110	350	17,0
150	350	18,0
200	350	19,0
110	375	21,0
160	375	23,0
220	375	25,0
130	430	30,0
180	430	31,0
240	430	34,0
130	515	38,0
190	515	41,0
250	515	44,0
140	580	54,0
200	580	59,0
260	580	65,0
150	630	70,0
210	630	75,0
280	630	80,0
180	680	95,0
230	680	100,0
320	680	110,0
190	785	120,0
240	785	125,0
330	785	140,0
190	895	150,0
240	895	160,0
330	895	175,0
190	1 000	180,0
220	1 000	185,0
290	1 000	200,0
230	1 115	225,0
230	1 115	225,0
290	1 115	235,0
280	1 215	275,0
280	1 215	270,0
300	1 215	275,0

PN 2,5

Jmenovitá světlost Nominal diameter	Jmenovitá světlost Nominal diameter	Úhlový posuv Angular movement	Ohybová tuhost Angular spring rate	Třecí moment Frictional moments
DN	DN	± deg (°)	N.m/°	N.m/bar
mm	inch			
1000	40"	1,5	3 886,0	315,0
1000	40"	2,0	2 590,0	315,0
1000	40"	3,0	1 727,0	315,0
1100	44"	1,5	4 722,0	381,0
1100	44"	2,0	3 148,0	381,0
1100	44"	3,0	2 099,0	381,0
1200	48"	1,5	5 108,0	543,0
1200	48"	2,0	3 405,0	543,0
1200	48"	3,0	2 270,0	543,0
1300	52"	1,0	4 126,0	642,0
1300	52"	1,5	3 094,0	642,0
1300	52"	3,0	2 063,0	642,0
1400	56"	1,0	5 103,0	740,0
1400	56"	1,5	3 828,0	740,0
1400	56"	3,0	2 552,0	740,0
1500	60"	1,0	6 225,0	985,0
1500	60"	1,5	4 668,0	985,0
1500	60"	3,0	3 112,0	985,0
1600	64"	1,0	7 497,0	1 116,0
1600	64"	1,5	4 498,0	1 116,0
1600	64"	3,0	3 749,0	1 116,0
1800	72"	1,0	10 545,0	1 400,0
1800	72"	1,5	6 327,0	1 400,0
1800	72"	3,0	5 272,0	1 400,0
2000	80"	1,0	14 320,0	1 963,0
2000	80"	1,5	8 592,0	1 963,0
2000	80"	3,0	7 160,0	1 963,0
2200	88"	1,0	18 907,0	2 362,0
2200	88"	1,5	11 344,0	2 362,0
2200	88"	3,0	9 453,0	2 362,0
2400	96"	1,0	30 269,0	3 158,0
2400	96"	1,5	18 162,0	3 158,0
2400	96"	3,0	15 135,0	3 158,0
2600	104"	1,0	38 252,0	4 101,0
2600	104"	1,5	22 951,0	4 101,0
2600	104"	3,0	19 126,0	4 101,0
2800	112"	1,0	57 498,0	4 730,0
2800	112"	1,5	34 499,0	4 730,0
2800	112"	3,0	28 749,0	4 730,0
3000	120"	1,0	34 912,0	6 509,0
3000	120"	1,5	34 912,0	6 509,0
3000	120"	3,0	29 093,0	6 509,0
3200	128"	1,0	70 339,0	7 386,0
3200	128"	1,5	42 203,0	7 386,0
3200	128"	3,0	35 169,0	7 386,0



MWP



MFP

Stavební délka Overall length	Šířka Width	Přibližná hmotnost App. weight	Stavební délka Overall length	Šířka Width	Přibližná hmotnost App. weight
mm	mm	kg	mm	mm	kg
690	1 260	365,0	760	1 260	615,0
740	1 260	380,0	810	1 260	630,0
810	1 260	405,0	880	1 260	650,0
690	1 370	505,0	760	1 370	695,0
740	1 370	520,0	810	1 370	710,0
810	1 370	540,0	880	1 370	735,0
710	1 475	635,0	790	1 475	775,0
760	1 475	655,0	840	1 475	795,0
830	1 475	680,0	910	1 475	820,0
770	1 635	740,0	850	1 635	940,0
810	1 635	755,0	890	1 635	955,0
890	1 635	785,0	970	1 635	990,0
770	1 735	780,0	850	1 735	995,0
810	1 735	800,0	890	1 735	1 015,0
890	1 735	830,0	970	1 735	1 050,0
810	1 835	855,0	890	1 835	1 165,0
850	1 835	875,0	930	1 835	1 185,0
930	1 835	910,0	1 010	1 835	1 220,0
850	1 995	995,0	930	1 995	1 325,0
930	1 995	1 035,0	1 010	1 995	1 370,0
970	1 995	1 055,0	1 050	1 995	1 390,0
890	2 195	1 150,0	980	2 195	1 600,0
970	2 195	1 195,0	1 060	2 195	1 645,0
1 010	2 195	1 220,0	1 100	2 195	1 670,0
910	2 395	1 305,0	1 010	2 395	1 850,0
990	2 395	1 355,0	1 080	2 395	1 895,0
1 030	2 395	1 380,0	1 120	2 395	1 925,0
970	2 595	1 465,0	1 070	2 595	2 245,0
1 050	2 595	1 520,0	1 150	2 595	2 300,0
1 090	2 595	1 545,0	1 190	2 595	2 330,0
1 050	2 805	1 685,0	1 170	2 805	2 650,0
1 130	2 805	1 755,0	1 240	2 805	2 715,0
1 170	2 805	1 795,0	1 280	2 805	2 750,0
1 090	3 065	2 015,0	1 210	3 065	3 125,0
1 170	3 065	2 100,0	1 290	3 065	3 210,0
1 210	3 065	2 145,0	1 330	3 065	3 255,0
1 130	3 255	2 175,0	1 250	3 255	3 655,0
1 210	3 255	2 260,0	1 330	3 255	3 745,0
1 250	3 255	2 305,0	1 370	3 255	3 790,0
1 280	3 465	2 670,0	1 410	3 465	4 240,0
1 280	3 465	2 670,0	1 410	3 465	4 240,0
1 320	3 465	2 720,0	1 450	3 465	4 285,0
1 250	3 725	2 980,0	1 390	3 725	4 820,0
1 330	3 725	3 085,0	1 470	3 725	4 925,0
1 370	3 725	3 140,0	1 510	3 725	4 980,0