

PN 25

Jmenovitá světllost Nominal diameter	Jmenovitá světllost Nominal diameter	Úhlový posuv Angular movement	Ohybová tuhost Angular spring rate	Třecí moment Frictional moments
DN	DN	± deg (°)	N.m/°	N.m/bar
mm	inch			
50	2"	6,0	2,4	0,5
50	2"	12,0	1,2	0,5
65	2 1/2"	6,0	2,3	0,8
65	2 1/2"	12,0	1,2	0,8
80	3"	3,0	3,2	1,1
80	3"	6,0	1,9	1,1
80	3"	12,0	1,4	1,1
100	4"	3,0	20,0	1,8
100	4"	6,0	11,0	1,8
100	4"	12,0	7,8	1,8
125	5"	3,0	71,0	3,4
125	5"	6,0	40,0	3,4
125	5"	12,0	27,0	3,4
150	6"	3,0	135,0	5,8
150	6"	6,0	75,0	5,8
150	6"	12,0	52,0	5,8
200	8"	3,0	169,0	9,6
200	8"	6,0	94,0	9,6
200	8"	12,0	65,0	9,6
250	10"	3,0	268,0	17,0
250	10"	6,0	149,0	17,0
250	10"	12,0	103,0	17,0
300	12"	2,0	375,0	24,0
300	12"	4,0	209,0	24,0
300	12"	6,0	144,0	24,0
350	14"	2,0	374,0	33,0
350	14"	4,0	208,0	33,0
350	14"	6,0	144,0	33,0
400	16"	2,0	908,0	43,0
400	16"	4,0	649,0	43,0
400	16"	6,0	413,0	43,0
500	20"	2,0	1 787,0	82,0
500	20"	4,0	1 276,0	82,0
500	20"	6,0	812,0	82,0
600	24"	2,0	2 708,0	139,0
600	24"	4,0	1 934,0	139,0
600	24"	6,0	1 231,0	139,0
700	28"	1,5	6 840,0	221,0
700	28"	2,0	4 560,0	221,0
700	28"	4,0	3 040,0	221,0
800	32"	1,5	9 095,0	327,0
800	32"	2,0	6 063,0	327,0
800	32"	4,0	4 042,0	327,0
900	36"	1,5	11 547,0	461,0
900	36"	2,0	7 698,0	461,0
900	36"	4,0	5 132,0	461,0



MWP

Stavební délka Overall length	Šířka Width	Přibližná hmotnost App. weight
mm	mm	kg
260	240	17,0
310	240	18,0
310	250	20,0
360	250	21,0
310	270	22,0
350	270	23,0
390	270	24,0
340	330	43,0
390	330	45,0
450	330	48,0
340	360	54,0
400	360	58,0
450	360	60,0
370	400	70,0
430	400	75,0
490	400	80,0
390	480	105,0
460	480	115,0
520	480	120,0
400	550	160,0
470	550	170,0
530	550	180,0
440	600	195,0
510	600	210,0
590	600	220,0
470	660	285,0
540	660	300,0
620	660	315,0
560	780	415,0
610	780	425,0
710	780	450,0
580	900	600,0
630	900	620,0
730	900	650,0
600	1 050	885,0
650	1 050	910,0
750	1 050	955,0
600	1 180	1 150,0
660	1 180	1 185,0
740	1 180	1 235,0
620	1 370	1 615,0
680	1 370	1 660,0
760	1 370	1 720,0
1 280	1 305	1 675,0
1 340	1 305	1 725,0
1 420	1 305	1 790,0



MFP

Stavební délka Overall length	Šířka Width	Přibližná hmotnost App. weight
mm	mm	kg
130	235	12,0
160	235	13,0
140	255	15,0
180	255	16,0
140	270	18,0
170	270	18,0
210	270	19,0
140	375	28,0
200	375	31,0
250	375	34,0
170	410	40,0
200	410	42,0
250	410	45,0
190	440	50,0
220	440	52,0
280	440	57,0
190	515	70,0
240	515	75,0
300	515	85,0
220	635	110,0
260	635	115,0
320	635	125,0
220	695	125,0
280	695	135,0
350	695	145,0
250	765	180,0
310	765	190,0
380	765	205,0
280	830	240,0
330	830	250,0
440	830	275,0
300	940	345,0
350	940	365,0
460	940	400,0
350	1 125	510,0
370	1 125	520,0
480	1 125	575,0
390	1 240	660,0
390	1 240	665,0
460	1 240	710,0
440	1 435	940,0
440	1 435	950,0
480	1 435	985,0
1 400	1 305	2 330,0
1 450	1 305	2 370,0
1 530	1 305	2 440,0

PN 25

Jmenovitá světlost Nominal diameter	Jmenovitá světlost Nominal diameter	Úhlový posuv Angular movement	Ohybová tuhost Angular spring rate	Třecí moment Frictional moments
DN	DN	± deg (°)	N.m/°	N.m/bar
mm	inch			
1000	40"	1,5	13 658,0	632,0
1000	40"	2,0	9 105,0	632,0
1000	40"	3,0	6 070,0	632,0
1100	44"	1,5	16 593,0	918,0
1100	44"	2,0	11 062,0	918,0
1100	44"	3,0	7 375,0	918,0
1200	48"	1,5	17 835,0	1 083,0
1200	48"	2,0	11 890,0	1 083,0
1200	48"	3,0	7 927,0	1 083,0
1300	52"	1,0	31 961,0	1 284,0
1300	52"	1,5	23 971,0	1 284,0
1300	52"	3,0	15 981,0	1 284,0
1400	56"	1,0	51 468,0	1 722,0
1400	56"	1,5	38 601,0	1 722,0
1400	56"	3,0	25 734,0	1 722,0
1500	60"	1,0	62 788,0	1 966,0
1500	60"	1,5	47 091,0	1 966,0
1500	60"	3,0	31 394,0	1 966,0
1600	64"	1,0	75 655,0	2 385,0
1600	64"	1,5	45 393,0	2 385,0
1600	64"	3,0	37 828,0	2 385,0



MWP



MFP

Stavební délka Overall length	Šířka Width	Přibližná hmotnost App. weight	Stavební délka Overall length	Šířka Width	Přibližná hmotnost App. weight
mm	mm	kg	mm	mm	kg
1 390	1 410	2 030,0	1 510	1 410	2 915,0
1 440	1 410	2 085,0	1 570	1 410	2 970,0
1 520	1 410	2 160,0	1 650	1 410	3 050,0
1 470	1 580	2 575,0	1 590	1 580	3 615,0
1 520	1 580	2 635,0	1 650	1 580	3 685,0
1 600	1 580	2 730,0	1 730	1 580	3 780,0
1 530	1 685	3 135,0	1 670	1 685	4 405,0
1 580	1 685	3 205,0	1 720	1 685	4 470,0
1 660	1 685	3 315,0	1 800	1 685	4 575,0
1 660	1 815	3 870,0	1 810	1 815	5 315,0
1 700	1 815	3 930,0	1 850	1 815	5 370,0
1 790	1 815	4 060,0	1 940	1 815	5 505,0
1 730	1 915	4 755,0	1 880	1 915	6 405,0
1 770	1 915	4 825,0	1 920	1 915	6 475,0
1 860	1 915	4 975,0	2 010	1 915	6 625,0
1 790	2 015	5 300,0	1 940	2 015	7 070,0
1 830	2 015	5 380,0	1 990	2 015	7 160,0
1 920	2 015	5 540,0	2 070	2 015	7 305,0
1 850	2 175	6 225,0	2 010	2 175	8 345,0
1 930	2 175	6 400,0	2 100	2 175	8 530,0
1 980	2 175	6 495,0	2 140	2 175	8 615,0